

SSD Roadmap 2017-2020

	Description	F/F	Density (GB)	2017		2018				2019				2020			
				Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
NSS700T Series	3D TLC	2.5" SATA ¹	128/256/512/1TB/2TB														3D TLC
NSS700L/NSS700K, NSS900K/NSS900J Series	TLC, 15nm MLC/pSLC	2.5" SATA ¹	32/64/128/256/512/1TB														
NSM260K Series	15nm MLC	M.2 2260	16/32/64/128														
NSN280N Series	3D TLC NVMe	M.2 2280	128/256/512/1TB														3D TLC
NSMS51U Series ²	19nm MLC	mSATA	32/64/128														<i>Contact Factory</i>
NSMS51J Series	15nm pSLC	mSATA	4/8/16/32/64/128/256														

 MP, Standard Extended Test Operating Temperature: 0°C to 70°C

Industrial Operating Temperature: -40°C to 85°C

ET and IT support

Power Loss Protection and pSLC (pseudo-SLC) Mode, Optional

 Standard Extended Test Operating Temperature: 0°C to 70°C

Power Loss Protection is standard with NSS700T Series; PLP not available with NSN280N Series

¹ 2.5" SATA available in 7mm and 9.5mm widths (NSS7* = 7mm; NSS9* = 9.5mm)

² Contact the factory to request mSATA MLC parts