



SSD Roadmap 2017-2020

	Description	F/F	Density (GB)	2017		2018				2019				2020					
				Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4		
NSS700T Series	3D TLC	2.5" SATA ¹	128/256/512/1T/2T							3D TLC									
NSS700K & NSS900K Series	15nm MLC	2.5" SATA ¹	32/64/128/256/512/1T	[Green bar]															
NSM260K Series	15nm MLC	M.2 2260	16/32/64/128	[Green bar]															
NSMS51U Series ²	19nm MLC	mSATA	32/64/128	<i>Contact Factory</i>															
NSMS51J Series	15nm pSLC	mSATA	4/8/16/32/64/128/256	[Green bar]															

-  MP, Standard Extended Test Operating Temperature: 0°C to 70°C
Industrial Operating Temperature: -40°C to 85°C
ET and IT support
Power Loss Protection, Optional
pSLC Mode (pseudo-SLC), Optional

-  Standard Extended Test Operating Temperature: 0°C to 70°C
Power Loss Protection, Standard

¹ 2.5" SATA available in 7mm and 9.5mm widths (NSS7* = 7mm; NSS9* = 9.5mm)

² Contact the factory to request mSATA MLC parts