

Computer Memory Test Labs Intel® Approved Final Test Report

MOTHERBOARD	MANUFACTURER	CHIPSET	TEST #	STATUS
DN2820FYK/DN2820FYKH	Intel	Intel® N2820	027135	PASSED

MEMORY MODULE INFORMATION

CMTL Part #: ITC002

Manufacturer Name: Insignis Technology Corporation, Inc.

Manufacturer Part #: NMLS0110-8KIT (i-Temp)

DRAM Manufacturer: INSIGNIS Environment Code: RoHS-Halogen Free

DRAM Part #: NDL18PFH-8KIT Low Profile: 30mm LP

Module Config: 128M x 64 Cas Latency: 11

Module Size: 1GB

PCB Part #: KOD38SRCB V0.55 Bank:1

PCB Layer Count: 6 Layer Assembly Type: JEDEC Standard/Non-stacked DRAM

Module Information: Unbuffered 1.35V Non-ECC 1600MHz DDR3 SODIMM

SYSTEM INFORMATION		TESTING DETAILS 35°C~55°C Temperature / Standard Voltage		
MINIMUM SYSTEM INFORMATION Minimum System: DN2820FYK/DN2820FYKH				
Serial Number: Board Revision:	G6YK4020043E H24582-201	Start Date:	6/5/2017	
Bios Memory Count:	1GB	Stop Date:	6/5/2017	
Processor Code: Bios at time of test:	Intel® Celeron® N2820 @ 2.13GHz FYBYT10H.86A.0052	Insertion Test:	Pass	
RST PRO Count:	928M	SPD Check:	Pass	
MAXIMUM SYSTEM INFORMATION		Minimum Load:	Pass	
Maximum System: Serial Number:	DN2820FYK/DN2820FYKH G6YK402004AZ	Maximum Load:	Pass	
Board Revision:	H24582-201	S0 ~ S5 Test:	Pass	
Bios Memory Count: Processor Code:	1GB Intel® Celeron® N2820 @ 2.13GHz	Power Cycle Test:	Pass	
Bios at time of test: R.S.T PRO Count:	FYBYT10H.86A.0052 928M	Test Card Version:	R.S.T Premium v8.50	

Microsoft Windows-7 64bit version is used as it support over 4GB memory and must support target chipset/CPU platform. All board drivers must be loaded when drivers are available on Intel web site. Front panel power cycling test, ACPI S3 sleep state cycling test, and Hibernate S4/S5 state cycling test is done up to 20 cycle each when the board support it. At least 2 loops of all test under R.S.T PRO3 to be completed.

Test Notes:

Max configuration, 5 Loops Passed, 0 Error; Memory speed running @ 1066MHz

This NUC Supports Intel® Braswell Chipset

UUT under test reached +50°C

This memory part was tested and Industrial certified at -40°C & +85°C without any error