

## NSEC Series Embedded Multimedia Card (eMMC)

### Overview

Insignis Technology Corporation eMMC products follow the JEDEC eMMC 5.0 standard. It is an ideal universal storage solution for many electronic devices, including embedded, automotive and industrial electronic applications requiring high quality, wide temperature operation and high reliability. eMMC encloses the MLC NAND and eMMC controller inside as one JEDEC standard package, providing a standard interface to the host. The eMMC controller directly manages NAND flash, including ECC, wear-leveling, IOPS optimization and read sensing.

### Features

- Packaged NAND flash memory with eMMC 5.0 interface
- Compliant with eMMC Specification Ver. 4.4, 4.41, 4.5, 5.0
- Bus mode
  - High-speed eMMC protocol
  - Clock frequency: 0-200MHz.
  - Ten-wire bus (clock, 1 bit command, 8 bit data bus) and a hardware reset.
- Supports three different data bus widths: 1 bit (default), 4 bits, 8 bits
  - Data transfer rate: up to 52Mbyte/s (using 8 parallel data lines at 52 MHz)
  - Single data rate: up to 200Mbyte/s @ 200MHz
  - Dual data rate: up to 400Mbyte/s @ 200MHz
- Operating voltage range:
  - VCCQ = 1.8 V/3.3 V
  - VCC = 3.3 V
- Error free memory access
  - Internal error correction code (ECC) to protect data communication
  - Internal enhanced data management algorithm
  - Solid protection of sudden power failure safe-update operations for data content
- Security
  - Support secure bad block erase commands
  - Enhanced write protection with permanent and partial protection options
- Quality
  - RoHS compliant
- Supports Field Firmware Update (FFU)
- Enhanced Device Life time
- Support Pre EOL information
- Optimal Size
- Supports Production State Awareness
- Supports Power Off Notification for Sleep
- Supports HS400
- Also available in p-SLC mode
- Temperature range
  - Operation:
    - Automotive: -40°C to 105°C
    - Industrial: -40°C to 85°C
    - Extended Test: 0 to 70°C
  - Storage:
    - -40°C to 125°C
- Component weight:
  - One unit of 4Gb eMMC 100 ball: 0.54g
  - One unit of 4Gb eMMC 153 ball: 0.37g
- JEDEC Standard Package with a 0.5mm pitch.

\* Engineering Specifications are available upon request by emailing [info@insignis-tech.com](mailto:info@insignis-tech.com)

## How to Order

## BGA100 Package

| Operating voltage           | Package | Option                 | NAND Density | Insignis Part Number |
|-----------------------------|---------|------------------------|--------------|----------------------|
| VCC=3.3V,<br>VCCQ=1.8V/3.3V | BGA100  | Extended Test          | 4GB          | NSEC00K004-ET        |
|                             |         |                        | 8GB          | NSEC00K008-ET        |
|                             |         |                        | 16GB         | NSEC00K016-ET        |
|                             |         |                        | 32GB         | NSEC00K032-ET        |
|                             |         |                        | 64GB         | NSEC00K064-ET        |
|                             |         | Industrial Temperature | 4GB          | NSEC00K004-IT        |
|                             |         |                        | 8GB          | NSEC00K008-IT        |
|                             |         |                        | 16GB         | NSEC00K016-IT        |
|                             |         |                        | 32GB         | NSEC00K032-IT        |
|                             |         |                        | 64GB         | NSEC00K064-IT        |
|                             |         | Automotive             | 4GB          | NSEC00K004-AT        |
|                             |         |                        | 8GB          | NSEC00K008-AT        |
|                             |         |                        | 16GB         | NSEC00K016-AT        |
|                             |         |                        | 32GB         | NSEC00K032-AT        |
|                             |         |                        | 64GB         | NSEC00K064-AT        |

## FBGA153 Package

| Operating voltage           | Package | Option                 | NAND Density | Insignis Part Number |
|-----------------------------|---------|------------------------|--------------|----------------------|
| VCC=3.3V,<br>VCCQ=1.8V/3.3V | FBGA153 | Extended Test          | 4GB          | NSEC53K004-ET        |
|                             |         |                        | 8GB          | NSEC53K008-ET        |
|                             |         |                        | 16GB         | NSEC53K016-ET        |
|                             |         |                        | 32GB         | NSEC53K032-ET        |
|                             |         |                        | 64GB         | NSEC53K064-ET        |
|                             |         | Industrial Temperature | 4GB          | NSEC53K004-IT        |
|                             |         |                        | 8GB          | NSEC53K008-IT        |
|                             |         |                        | 16GB         | NSEC53K016-IT        |
|                             |         |                        | 32GB         | NSEC53K032-IT        |
|                             |         |                        | 64GB         | NSEC53K064-IT        |
|                             |         | Automotive             | 4GB          | NSEC53K004-AT        |
|                             |         |                        | 8GB          | NSEC53K008-AT        |
|                             |         |                        | 16GB         | NSEC53K016-AT        |
|                             |         |                        | 32GB         | NSEC53K032-AT        |
|                             |         |                        | 64GB         | NSEC53K064-AT        |

Visit: <http://insignis-tech.com/how-to-buy>

\* Engineering Specifications are available upon request by emailing [info@insignis-tech.com](mailto:info@insignis-tech.com)

DISCLAIMER: All product, product specifications, and data are subject to change without notice to improve reliability, function or design, or otherwise. The information provided herein is correct to the best of Insignis Technology Corporation's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.